nutri**safe**2®

The safe enteral feeding system for Neonatology



10

HATOLOGY HATOLOGY






THE USER NEEDS

• "The very fragile preterm infants require supplementary characteristics for the medical devices compared to larger and more robust patients. [...] Very small volumes (less than 0,1 ml) are sometimes administered and require precise dosage possibilities."⁽¹⁾

THE CONCERN


- "Concerns have been raised about the possible risks of delivering accurate doses of medicines in certain clinical practices across high risk subpopulations (e.g. neonatal patients) when using a reversed connection system (female to male). This orientation may introduce inadvertent displacement of fluid ..."(1)
- "Laboratory testing also shows a mid tolerance E1 [ENFit] connector pair in a female to male orientation displaces a mean average of 0.150ml..."⁽¹⁾

To provide the best possible care and safety for neonatal patients, Vygon will continue to provide the nutrisafe2[®] system, which is compliant with ISO 80369-1.



...SMALL

In Neonatology, think SAFE, SMALL & ACCURATE!



VÝGON

nutri**safe**2®


| s minim | ises dead space: | | | |
|------------------------------------|------------------|--|--|--|
| fe2® | Reversed Luer | ENFit (ISO/DIS80369-3) | | |
| ml | 0.099ml | 0.191ml | | |
| ge adspace (Blue reduces the | | nutrisafe2® reduces the deadspace by 0% compared to ENFit ⁽²⁾ | | |
| | | | | |
| and ACCURATE | | | | |

| fe2® | Reversed Luer | ENFit (ISO 80369-3) | | |
|------------------------------------|-----------------------------------|------------------------|--|--|
| ml | 0.045ml | 0.120ml ⁽³⁾ | | |
| r ENFit, as written in ISO 80369-3 | | | | |
| ue to the feed | Feeding tube ing tube connection | | | |

Worldwide proven system

10YEARS OF EXPERIENCE IN NEONATOLOGY!

- Created in 2005, nutri**safe**2[®] is the first enteral feeding system totally incompatible with Luer and specially designed for premature babies.
- No reported misconnection
- Satisfied customers from 35 countries



For further information, please contact: questions@vygon.com

The specifications given in this brochure are for information only and are not, under any circumstances, of a contractual nature.

Vygon – 5, rue Adeline • 95440 ECOUEN • FRANCE Reception: +33 (0)1.39.92.63.63 – Service clients France: +33 (0)1.39.92.63.81 Export customer service: +33 (0)1.39.92.64.15 Fax: +33 (0)1.39.92.64.44 • www.vygon.com

